

# **B-SELF TAPE AL**

Bitumen Based, Self Adhesive, Waterproofing Tape

# Description

**B-SELF TAPE AL** is a bitumen based, cold applicable, one side coated with aluminum foil or colored mineral, other side is adhesive waterproofing tape.

# **Fields of Application**

It provides waterproofing with adhering on different substrates such as wood, metal, glass, plaster, concrete etc.

### **Features and Benefits**

- Aluminum foil and mineral coated top surface provides UV resistance.
- Applied easily even though inclined surface because of elasticity.
- Convenient with bituminous system.
- Self adhesive.
- Easy to applied.
- Applicable on wide range substrates.

#### Technical Data

|                | COCAL US LOW          |
|----------------|-----------------------|
| Content        | SBS Modified Bitumen  |
| Color          | Black                 |
| Thickness      | 1,5 m                 |
| Weight         | 1,7 kg/m <sup>2</sup> |
| Width          | 10-15-20-30-60 cm     |
| Length         | 10 m                  |
| Top Surface    | Aluminum Foil         |
| Bottom Surface | Removable Film        |
| HS Code        | 6807.10.00.00.00      |

# **B-SELF TAPE AL**

# Bitumen Based, Self Adhesive, Waterproofing Tape

### **Application Procedure**

#### **Preparation of Substrate**

Application surface must be dry, clean and clean off materials which prevent bonding, such as dust, oil, rust and remove loose pieces. High absorbent surfaces such as concrete, plaster, chipboard must be primed with **B PR 101** bituminous based primer.

#### **Application Method**

Peel the removable film layer of **B-SELF TAPE AL** and pressed firmly sticky surface on substrate. Tape should be fully contact with the substrate by pressing its every point on application surface.

#### **Packaging**

Width: 10-15-20-30 cm

Length: 10 m

#### **Shelf Life**

5 years in original, unopened package.

### Storage

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight.

#### **Cautions / Limitations**

- It may be harmful with skin contact.
- Do not apply in freezing conditions or during precipitation.
- Protect applied materials from rain, freezing, foot traffic and continuous high humidity until completely dry.
- Do not use when air and surface temperatures are below +5°C and above +35°C.
- Avoid heavy traffic for 24 hours.

# **B-SELF TAPE AL**

Bitumen Based, Self Adhesive, Waterproofing Tape

# Health and Safety

**Warning!** Cause eye and skin irritation. If eye or skin contact, get immediate medical attention. If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.

Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

**Limited Warranty:** This product is subject to a written limited warranty which can be obtained free of charge from BAUMERK Company. Please contact with technical service department for further information and support.

Tel: +90 212 438 7 888 Fax: +90 212 438 67 05