

FH RELEASE AGENT

Release Agent for Stamped Concrete Systems

Description

FH RELEASE AGENT is a release agent, in powder form, colored, antique appearance that can be used for cement based stamped concrete hardener.

Fields of Application

- Allows easily leave the polyurethane mold from the stamped concrete surfaces.
- Applied on colored surface hardener to give antique effect.

Features and Benefits

- Creates antique effect and appearance.
- Creates a decorative and aesthetic appearance with different colors.
- Prevents the adhesion of concrete to the mold surface.
- Allows to transfer of mold figures precisely on concrete surface hardeners.
- Prevents the mold to wear and tear.

Technical Data

Content	Pigmented, special powder mix
Color	Grey / Colored
Density	1,10 kg/L
Adhesion on Moulds / Concrete	None
HS Code	3816.00.00

Application Procedure

Preparation of Substrate

FH RELEASE AGENT application must be started after finished the surface hardener application and polishing.

Application Method

FH RELEASE AGENT is spreaded on the surface hardener applied surface and done figured process with using molds. Depends on weathering conditions after 1 or 2 days later, surface must be

FH RELEASE AGENT

Release Agent for Stamped Concrete Systems

washed with pressure water. Washed with high pressure water gives less antique appearance, on the contrary washed with low pressure water gives more deeply antique appearance.

Consumption

According to effect and figure on the surface 0,200 – 0,400 kg/m²

Packaging

6 kg plastic bucket

Shelf Life

12 months in original, unopened package.

Storage

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight.

Cleanup Information

Clean tools and equipment with water immediately after use. Dried material can only be removed mechanically.

Cautions / Limitations

- It may be harmful with skin contact.
- Do not apply in freezing conditions or during precipitation.
- Protect applied materials from rain, freezing, foot traffic and continuous high humidity until completely dry.
- Do not use when air and surface temperatures are below +5°C and above +35°C.

FH RELEASE AGENT

Release Agent for Stamped Concrete Systems

Health and Safety

Warning! Cause eye and skin irritation. If eye or skin contact, get immediate medical attention. If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.

Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

Limited Warranty: This product is subject to a written limited warranty which can be obtained free of charge from BAUMERK Company. Please contact with technical service department for further information and support.