

Technical Data Sheet

ANTI-FIRE

Fireproof Paint



Description

Synthetic based, fireproofing matt interior topcoat for wall, wood and metal surfaces. Normal painted surface burns within 5 minutes, **BAUMERK ANTI-FIRE** Paint extends this time for 2-3 hours due to special resin composition.

Application Areas

- Interior wall, wood and steel in buildings.
- High risk of fire areas such as hospital, school, airports.

Feature and Benefits

- Ensures perfect integration with the substrate without cracking, blistering and flacking.
- When exposed to heat and flame, ANTI-FIRE Fireproofing Paint acts as a thermal barrier between the fire and the substrate.
- Fire retardant.

Technical Information

Solvent Content Color Most colors Appearance Viscous liquid Thinning Ready to use Consumption $3,00 - 3,50 \text{ m}^2 / \text{L}$ Coat thickness | 100 – 200 micron dry film Recommended Coat | 2-3 coats Brush / Spray Application Tools Drying Time 2 hours to recoat Reaction to Fire Test Class: B S2 d0 (TS EN 13501-1:2013) Fire Extension Period 2-3 hours

Preparation of substrate

Application surfaces should be clean off the rust, dirt and moisture. Old painted surfaces should be sanded and cleaned.



ANTI-FIRE

Fireproof Paint

Application

Paint is ready to use. Minimum 2 hours curing needed for each coat.

Packaging

15 L metal pail

Shelf Life

12 months in original, unopened package

Storage

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight.

Cleanup Information

Clean tools and equipment with industrial type solvents immediately after use. Dried material can only be removed mechanically.

Cautions / Limitations

- Highly flammable material.
- It may be harmful with skin contact.
- Do not apply in freezing conditions or during precipitation.
- Protect applied materials from rain, freezing, foot traffic and continuous high humidity until completely dry.
- Do not use when air and surface temperatures are below +0°C and above +35°C.
- Avoid heavy traffic for 24 hours.
- Allow 4 weeks before washing or cleaning for full cure.

Health and Safety

Warning! Cause eye and skin irritation. If eye or skin contact, get immediate medical attention. If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.

www.baumerk.com



ANTI-FIRE

Fireproof Paint

Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

Limited Warranty: This product is subject to a written limited warranty which can be obtained free of charge from BAUMERK Company. Please contact with technical service department for further information and support.

Fax: +90 212 438 67 05

www.baumerk.com