


Technical Data Sheet

MARBLE BEACH

Marble Texture



Description

Water based, semi-gloss, marble appearance, ready to use decorative topcoat for interior surface.

Application Areas

- All previously painted surfaces.
- Interior surfaces such as concrete, plaster, fiber cement board, glass textile and wall paper.

Technical Information

Content	Acrylic emulsion
Color	Most colors
Appearance	Viscous liquid
VOC Content	110 g/L
Gloss	Class G2
Particle Size	Class S1
Weight Solid	68±2%
Thinning	Ready to use
Consumption	0,400 kg / m ² for two layers
Recommended Coat	2 coats
Application Tools	Trowel
Drying Time	2 hours to touch
	24 hours to full cure

Preparation of substrate

The application surface must be smooth, clean, dry and solid. Old painted, glass textile, or wall paper covered surfaces must be removed. Surface should be smoothed with applying **INPAST** Acrylic Interior Paste. After the paste applied surface is sanded, **PRIME C 1/7** Concentrated Primer diluted with water in the ratio of 1/7 (1 cup primer / 7 cup water) and applied to complete the surface preparation process. Due to its weak and chalking quality, sateen plaster should never be used on the surface.

1/3 Marble Beach

www.baumerk.com



Technical Data Sheet

MARBLE BEACH

Marble Texture

Application

Ready to use, do not diluted. After surface preparation, **MARBLE BEACH** Marble Texture Paint should be applied by using a trowel in a single layer without dilution. Second layer of application is applied on wet surface. The surface is smoothed out by circular motion applied through the sides moving from outside towards inside. After the surface dries, the third layer should be applied with a spatula in a patch pattern. Immediately following the application, and before the product is dry, the polishing process must be started with the help of a trowel. Application must be made with care without applying too much pressure on the surface. If too much pressure is applied on the surface, it will appear as a scratched surface. After the polishing process is completed, the surface must be allowed to dry for 24 hours.

Packaging

10 kg plastic bucket

Shelf Life

24 months in original, unopened package

Storage

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight.

Cleanup Information

Clean tools and equipment with water immediately after use. Dried material can only be removed mechanically.

Cautions / Limitations

- Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.
- Do not apply in freezing conditions or during precipitation.
- Protect applied materials from rain, freezing, foot traffic and continuous high humidity until completely dry.

2/3 Marble Beach

www.baumerk.com



Technical Data Sheet

MARBLE BEACH

Marble Texture

- Do not use when air and surface temperatures are below +0°C and above +35°C.
- Avoid heavy traffic for 24 hours.
- Allow 4 weeks before washing or cleaning for full cure.

Health and Safety

Warning! Cause eye and skin irritation. If eye contact, flush eyes with water for several minutes and remove contacts if present and easy to do. Get immediate medical attention. If skin contact; wash skin with plenty of soap and water. Get immediate medical attention. If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.

Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

Limited Warranty: This product is subject to a written limited warranty which can be obtained free of charge from BAUMERK Company. Please contact with technical service department for further information and support.