


Technical Data Sheet

PRIME-EX

Exterior Primer



Description

Acrylic emulsion-based exterior primer.

Application Areas

- Cementitious Stucco
- Concrete
- Gas concrete

Feature and Benefits

Applied as a primer on high porosity and absorptivity exterior walls of buildings that the purpose of increasing adherence and reducing consumption of final layer paint and coating.

Technical Information

Acrylic emulsion Content White Color Viscous liquid Appearance Particle Size Class S1 Solid Content 73±2 % Thinning Water $0.090 - 0.140 L / m^2$ Consumption Recommended Coat 1 coat Roller / Brush Application Tools Drying Time 2 hours to touch 12 hours to topcoat

Application

Primer is diluted with water in the ratio of 1/1 and mixed until it reaches a homogenous state. Primer should be applied as one layer with lambskin roller or brush. Paint or coating application should be started at least 12 hours later, after the application of primer. During application the

www.baumerk.com



PRIME-EX

Exterior Primer

surface and ambient temperature should be between +5°C and +30°C and protect the surface from frost.

Packaging

15 L / 2,5 L plastic bucket

Shelf Life

12 months in original, unopened package

Storage

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight.

Cleanup Information

Clean tools and equipment with water immediately after use. Dried material can only be removed mechanically.

Cautions / Limitations

- Stir thoroughly before using the paint and do not mix it with a paint of another trade-mark.
- Do not apply in freezing conditions or during precipitation.
- Protect applied materials from rain, freezing, foot traffic and continuous high humidity until completely dry.
- Do not use when air and surface temperatures are below 0°C and above +35°C.
- Avoid heavy traffic for 24 hours.
- Allow 4 weeks before washing or cleaning for full cure.

Health and Safety

Warning! Cause eye and skin irritation. If eye contact, flush eyes with water for several minutes and remove contacts if present and easy to do. Get immediate medical attention. If skin contact; wash skin with plenty of soap and water. Get immediate medical attention. If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.

www.baumerk.com



PRIME-EX

Exterior Primer

Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

Limited Warranty: This product is subject to a written limited warranty which can be obtained free of charge from BAUMERK Company. Please contact with technical service department for further information and support.

Tel: +90 212 438 7 888 Fax: +90 212 438 67 05