

B-ROD

Backer Rod for Joints

Description

B-ROD is a backer rod for joints that produced with polyethylene.

Fields of Application

- It is used for waterproofing sealants in joints and dilatations.
- It is used as filler in the joint of between doors, windows and walls.

Features and Benefits

- Elastic and compressed easily.
- Waterproof and water impermeable.
- Odourless.
- Decreases consumption of sealants in the joints.

Technical Data

Color	Grey / other colors producible
Density	25-30 g/cm ³
Water Vapor Transmission	μ≥3500
Water Absorption	1,6% (after 28 days)
Service Temperature	-40°C to +100°C
HS Code	3925.90.80.00.00

Application Procedure

Application Method

Easy to apply. Backing rod must be 30% more thick than width of joint and it should be placed into the joint by compressing. Then, surface is coated with sealants as polyurethane, polysulphide, acrylic etc.

Packaging

Diameter of **B-ROD** is from 6 mm to 100 mm.

B-ROD

Backer Rod for Joints

Shelf Life

Unlimited.

Storage

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight.

Cautions / Limitations

- It may be harmful with skin contact.
- Do not apply in freezing conditions or during precipitation.
- Protect applied materials from rain, freezing, foot traffic and continuous high humidity until completely dry.

Health and Safety

Warning! Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

Limited Warranty: This product is subject to a written limited warranty which can be obtained free of charge from BAUMERK Company. Please contact with technical service department for further information and support.