

Technical Data Sheet

## COURT PAINT

Tennis Court Paint



#### Description

Water based, matt, court and floor paint.

#### **Application** Areas

- Tennis court
- Mineral surface
- Foot traffic areas; hall, corridor, warehouse, carpark etc.

#### eature and Benefits

- Ensures perfect integration with the substrate without cracking, blistering and flacking.
- Excellent adhesion and hiding power capacity.
- Resistant to atmospheric conditions.
- Do not discoloration and yellowing.

#### **Fechnical Information**

_	
Content	Acrylic emulsion
Color	Most colors
Appearance	Viscous liquid
Gloss	Class G4
Particle Size	Class S1 (TS 7847)
Weight Solid	70±2%
Thinning	Water
Consumption	0,400 kg / m <sup>2</sup>
Recommended Coat	2 -3 coats
Application Tools	Brush / Roller
Drying Time	2 hours to touch
	6 hours to recoat
	24 hours to full cure

1/3 Court Paint



Technical Data Sheet

# COURT PAINT

**Tennis Court Paint** 

#### Preparation of substrate

Application surfaces should be dry, oil-free and clean. Paint is used as a primer before the application with diluted water in the ratio of 1/1.

#### Application

Paint should be diluted with water in the ratio of 1/1 and applied as a primer. Then paint should be applied for second and third coats with diluted 10% water by using roller or brush.

#### Packaging

20 kg plastic bucket

#### Shelf Life

24 months in original, unopened package

#### Storage

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight.

#### **Cleanup Information**

Clean tools and equipment with water immediately after use. Dried material can only be removed mechanically.

#### Cautions / Limitations

- Do not overcoat with solvent based materials.
- Do not apply in freezing conditions or during precipitation.
- Protect applied materials from rain, freezing, foot traffic and continuous high humidity until completely dry.
- Do not use when air and surface temperatures are below +0°C and above +35°C.
- Avoid heavy traffic for 24 hours.
- Allow 4 weeks before washing or cleaning for full cure.



Technical Data Sheet

### COURT PAINT Tennis Court Paint

#### Health and Safety

**Warning!** Cause eye and skin irritation. If eye contact, flush eyes with water for several minutes and remove contacts if present and easy to do. Get immediate medical attention. If skin contact; wash skin with plenty of soap and water. Get immediate medical attention. If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.

Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

**Limited Warranty**: This product is subject to a written limited warranty which can be obtained free of charge from BAUMERK Company. Please contact with technical service department for further information and support.

**Baumerk Yapı ve Kimya San. Tic. Ltd. Şti.** Dursunköy Mah. Uygur Cad. No 44 Hadımköy, 34555 ARNAVUTKÖY / İSTANBUL / TÜRKİYE Tel: +90 212 438 7 888 Fax: +90 212 438 67 05